

4350FCT & 4351FCT Top Handle & Barrel Body Jig Saws

720W



Low noise & low vibration

MAKITA ADVANTAGE

- New exterior design features high metal to plastic ratio.
- Employs lightweight rod and balance plate mechanism to reduce vibration dramatically.
- Constant speed control keeps minimizing the speed loss under loaded conditions.
- Soft Start suppresses the shock when starting.
- Rigid Aluminium base can be tilted up to 45° to the left or right.
- Can be connected to vacuum with optional dust nozzle and hose complete 28-5.
- Plastic cover plate can be attached quickly without using tools to protect surfaces of delicate materials such as plastics & decorative veneers.

SPECIFICATIONS: Length of stroke Maximum cutting capacities	4350FCT / 4351FCT 26mm	OPTIONAL ACCESSORIES: Description	Part No.
In wood at 90° In steel at 90° Strokes per minute Continuous rating input Overall dimensions Net weight Power supply cord	135mm 10mm 800 - 2 800 720W 236x73x207mm / 271 x 73 x 187mm 2.6kg / 2.5kg 2.5m	Bayonet fitting blades: No. 51 HSS bladefor stainless steel & tough plastics No 58 HCS blade for fast cutting No. 59 HCS blade for fast finish work B-16 HCS blade for fast cutting B-19 HSS blade for tough plastics & decorative veneers B-22 HSS blade for stainless steel & tough plastics B-23 HSS blade for stainless steel & tough plastics	792434-8 792426-7 792427-5 792517-4 792520-5 792522-1 792523-9
Carbon brush	CB419	B-26 HSS blade for scrolling in hardwoods	792526-3
FEATURES: Double insulation, dust collecting, orbital cutting Bayonet shank jig saw blade, electronic speed control, variable speed, soft start, built-in job light & carry case. BR-13 HCS blade for spliter-free cuts requiring no sand B-16-L HCS blade for cutting thick material 1.4m guide rail 3.0m guide rail Guide rail adaptor set		A-02294 792726-5 194368-5 194367-7 193517-1	
STANDARD EQUIPME Jig saw blade set Hex wrench Cover plate	ENT:	Guide rule set Anti-splintering device Cover plate Dust nozzle Hose complete 28-5	193516-3 192557-6 417852-6 417853-4 A-34229