



# Cordless Hammer Driver Drill Cordless Impact Driver

Satisfy Professional's Needs

**LXT**  
LITHIUM-ION



**18V**  
LITHIUM-ION

**XPT**  
EXTREME PROTECTION TECHNOLOGY

Cordless Hammer Driver Drill  
DHP482ZJ



Cordless Hammer Driver Drill  
DHP482ZJ

**1,900** High Speed

Predecessor model: 1,500



DTD152Z

**High Speed**

Cordless Impact Driver  
DTD152Z



**2,900** High Speed

Predecessor model: 2,300

## Compact overall length for increased maneuverability

← 198mm DHP482ZJ →

### LED Job light with pre-glow functions

On pulling switch trigger, the light automatically turns on before motor starts turning.



### Compact belt clip

**XPT**  
EXTREME PROTECTION TECHNOLOGY

For use in outdoor applications or harsh environments, protection from dust and dripping water is enhanced.

**18V LITHIUM-ION**

### Battery

BL1850: 5.0Ah

BL1830: 3.0Ah

BL1815N: 1.5Ah



### Fast Charger

DC18RC

Charging time 22min.



DC18SE (Automotive)

Charging time (3.0Ah)

60minutes



## More Torque

DTD152Z: 165Nm

Predecessor model: 160Nm

DHP482ZJ: 62Nm

Predecessor model: 50Nm (Hard Joint)

### Ergonomically designed handle with soft grip



**A** In order to provide maximum thrust to the bit, the top back of the handle is ergonomically contoured and widened according to the U-shape formed between user's thumb and index finger.

**B** Rubberized soft grip provides comfortable grip and more control while minimizing hand fatigue and pain.

### All metal gear construction

All metal gear construction for extra-high transmission durability

(DHP482ZJ)



### 21 stages Torque Settings

(DHP482ZJ)

Predecessor model: 16 stages



## Cordless Hammer Driver Drill

**DHP482ZJ 13mm**

440

- Variable Speed
- Brake
- Reversing
- Mechanical 2-Speed
- Keyless Chuck
- Torque Setting 21
- Built-in Job Light
- Carrying Case



	DHP482ZJ
Capacity	Steel: 13mm Wood: 38mm Masonry: 13mm
Impacts per minute (i/min)	Hi: 0-28,500 Lo: 0-9,000
No load speed (r/min)	Hi: 0-1,900 Lo: 0-600
Max. fastening torque	Hard / Soft: 62 / 36Nm
Dimensions (L x W x H)	198x79x249mm
Net Weight*	1.5kg with BL1815N 1.8kg with BL1850

Standard Equipment :Fast Charger, Battery Cartridge, ( + ) ( - ) Bit, Belt clip

## Cordless Impact Driver

**DTD152Z**

448

- Variable Speed
- Brake
- Reversing
- Built-in Job Light



Capacity	Machine screw: M4 - M8 Standard bolt: M5 - M16 High tensile bolt: M5 - M12 Coarse thread (in length): 22 - 125mm
Impacts per minute (i/min)	0 - 3,500
No load speed (r/min)	0 - 2,900
Max. fastening torque	165Nm
Dimensions (L x W x H)	137x79x238mm
Net Weight*	1.3kg with BL1815N 1.5kg with BL1850

Standard Equipment :

\*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

# Batteries and Charger Not Included!