

TW0200 &

TW0200 380W TW0350 **400W**

- 1. Extra rigid internal aluminium gear case and hammer case.
- 2. Externally accessible carbon brushes for easy replacement.
- 3. Ergonomic palm fitting soft grip
- 4. 2-Speed selection
- 5. Push button switch

Conveniently located to selected forward / reverse operation.

6. Large trigger switch

for easy to control variable speed.

7. Detachable belt clip (TW0200)

Can be attached on either left or right of the impact wrench with the use of any tools.

8. Rocker Switch (TW0350)

for easy reversing.





200 N-m

Max Torque

SPECIFICATIONS: TW0200 TW0350

Capacities Standard bolt M10-M16 M12-M22 High tensile bolt M10-M12 M12-M16 12.7mm 12.7mm Square drive Impacts per minute 0 - 2,200 2,000 400W Continuous rating input 380W 0 - 2,200r/min No load speed 2.000 Max. Fastening Torque 200Nm 350Nm Overall length 251mm 282mm Net weight 2.2kg 2.9kg Power supply cord 2.5m 2.5m Carbon brush AC411 AC411

TW0350 350 N-m **Max Torque**

FEATURES:

Double insulation Double insulation Reverse Reverse Variable speed Carry case Carry case

STANDARD EQUIPMENT:

Socket Socket

OPTIONAL ACCESSORIES:		
Description	Part No.	Part No.
100mm extension bar	134874-8	134874-8
For work in narrow spaces		
where the socket cannot reach.		
84mm universal joint	134877-2	134877-2
For use in limited space		
where the tool cannot be		
held in line with the axis of the		
bolt or nut.		
Bit adaptor assembly	134873-0	134873-0
For use with 1/4" hex bits		

