



GD0600

6.35mm Die Grinder

400W

Superior Heat Resistance

Low noise design
Noise level under no load
7.3dB

Small circumference housing
for comfortable and
easy handling

Stepped neck of solid aluminium housing

By removing the insulation cover the following optional
accessories can be attached to the neck:

1. Vice holder at 35mm diameter portion of the neck
2. Drill stand at the 43mm diameter portion of the neck
3. Side handle at the 43mm diameter portion of the neck

Insulation cover

Round-shaped collet nut


Reduces the possibility of damage / scratches
to the workpiece compared to the conventional
hex-type collet cones

Vent slots

Designed to direct the
exhaust air stream
towards the side
away from the operator.



Dust proof motor section
with protective zigzag varnish
on armature coil and protective
powder varnish-coating
on field coil



Paddle type on / off switch

Allows for easy one-hand operation.

Anti-slip lever surface ensures perfect on/off control.

The lock-off switch is positioned in the center of the paddle lever,
so that it is operable no matter what portion of the lever is gripped.



SPECIFICATIONS:

Collet capacity	6.35mm
Wheel diameter	38mm
No load speed	25 000 r/min
Continuous rating input	400W
Overall dimensions (L X W X H)	358mm x 82mm x 82mm
Net weight	1.7kg
Power supply cord	2.5m
Carbon brush	CB325

FEATURES:

Double insulation

STANDARD EQUIPMENT:

Wrench (Tool does not come with wheel point or flapper wheel)

OPTIONAL ACCESSORIES

Description	Part No.
Collet Cone	763620-8
17mm Wrench	781008-0

