


# Straight Grinder GS5000 125mm (5")



Ergonomically design handle and barrel for added extra maneuverability.

# Lightweight with large soft grip reduce operator's fatigue.



with rubberized cover



# Improved durability of gears

about two times as tough as the current by;


- (1) Change of the grease
- (2) Modification on the inside of Gear housing for grease to stay on Gears teeth.

### Dust cover attachment set


(optional accessory) Part No. 195059-1 protect motor from metal dust.








provides comfortable and sure grip.





makita (

protect commutator when carbon brush wears out.



Hanger bracket

can be attached for continuous use with less fatigue.

(optional accessory) Part No. 342004-9



## Large type trigger switch



with a lever for lock-off and lock-on in compliance with the requirement\*\* of the new IEC regulations (for Europe)

By pushing the lever forward, the switch is released from Lock-off position. By pulling the lever backward, the switch is locked on.

\*\*The lock lever is required to have two different actions for releasing the switch from Lock-off position and locking the switch on.

### Accessories

with the regulations.


Wheel cover in compliance

### Grinding wheel

(EN): EN 12413 \* ANSI B71







| Size (mm)         | Grit | General Label<br>Part No. | North America Label Part No. |
|-------------------|------|---------------------------|------------------------------|
| For Model: GS5000 |      |                           |                              |
| 125 x 20 x 12.7   | A24P | B-33990                   | -                            |
| 125 x 20 x 12.7   | A36P | B-34001                   | -                            |
| 125 x 20 x 20     | A24P | -                         | B-34039                      |
| 125 x 20 x 20     | A36P | -                         | B-34045                      |
| 125 x 20 x 20     | A24P | B-28662 (EN)              | B-28852*                     |
| 125 x 20 x 20     | A36P | B-28678 (EN)              | B-28868*                     |

| GS5000 125mm (5")       |                            | 204 |
|-------------------------|----------------------------|-----|
|                         |                            |     |
| Continuous rating Input | 750W                       |     |
| Wheel diameter          | 125mm (5")                 |     |
| Hole dia.               | 12.7mm (1/2"), 20mm (3/4") |     |
| No load speed (rpm)     | 5,600                      |     |
| Dimensions              | 590x189x116mm              |     |
| (L x W x H)             | (23-1/4"x7-7/16"x4-9/16")  |     |
| Net Weight*             | 5.0kg (11.1lbs)            |     |
| Power supply cord       | 2.5m (8.2ft)               |     |
|                         |                            |     |

\*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.

