



Satisfy Professional's Needs

**Nibbler**  
**JN3201J** 3.2mm

## High cutting capacity

Steel up to 400 N/mm<sup>2</sup> : 3.2mm

Steel up to 600 N/mm<sup>2</sup> : 2.5mm

Steel up to 800 N/mm<sup>2</sup> : 1.0mm

Aluminum up to 200 N/mm<sup>2</sup> : 3.5mm



# 710W continuous rating input

Low noise level at only 81dB(A)

Ergonomically designed handle with rubberized soft grip

provides comfortable grip and more control while minimizing hand fatigue and pain.

## Gauge

The groove on the yoke serves as a thickness gauge for shearing mild or stainless steel plate. If the material fits within the groove, it is shearable.

Steel up to 600 N/mm<sup>2</sup>: 2.5mm



Steel up to 600 N/mm<sup>2</sup>: 3.5mm



## On-tool storage for hex wrench

Hex wrench can be stored on the model for operator's convenience.

## Part standardization

Blade section : same as Nibbler JN3200



## Die

Part No. 792292-2




## Punch

Part No. 792728-1



## Wrench 50

Part No. 781019-5




## Washer

Part No. 341796-7

(To keep clearance of 3.5 to 4.0mm, use a washer or two under the die when installing a resharpened die.)

A. Die  
B. Washer



## Nibbler

### JN3201J 3.2mm

303 [mm]

Continuous rating Input Capacity	710W Steel up to 400 N/mm <sup>2</sup> : 3.2mm Steel up to 600 N/mm <sup>2</sup> : 2.5mm Steel up to 800 N/mm <sup>2</sup> : 1.0mm Aluminum up to 200 N/mm <sup>2</sup> : 3.5mm
Min. cutting radius	Outer edge : 128mm Inner edge : 120mm
Strokes per minute (s/min)	1,300
Dimensions (L x W x H)	225 x 90 x 254mm
Net Weight*	3.4kg
Power supply cord	2.5m

Double Insulation

Standard Equipment :  
Wrench 50, Hex wrench, Washer

\*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.