



Please see www.makita.co.za for detailed information on the shape, size, recommended use and material of each blade.

Cutting (plunge cutting)



Applications:

Cutting of various materials such as oak wood, drywalls, plastics, copper pipes, non-hardened nails, etc.

Benefits:

- Different from jig saws, etc, able to make a plunge cut in the wall for electrical connection box, lighting, exhaust fan, etc.
- The blade can be positioned in twelve different angles to allow easy operation in tight spaces.

Cutting



Applications:

Cutting of various materials such as oak wood, drywalls, plastics, copper pipes, non-hardened nails, etc.

Benefits:

- Able to perform long distance push cut.
- The segment shape allows flush cutting.

Sanding



Applications:

Wood sanding, concrete sanding, or paint removal, etc. with a variety range of abrasive papers.

Benefits:

- Able to sand in corners.
- Connectable to vacuum cleaner with optional dust extraction system.

Removing grout/ Cutting tiles



Applications:

Replacing broken wall or floor tile.

Benefits:

- Less amount of dust scattering thanks to oscillating action.
- The segment shape allows flush cutting.

Scraping



Applications:

Removing mortar, tile adhesive, hardened glue, window putty, caulking, paint, etc.

Benefits:

- Low-profile blade with a narrow tip allows easy removal of caulking, window putty, etc.

Battery

Model: BTM50ZK




BL1830:
18V 3.0Ah

BL1815:
18V 1.3Ah

Charger

DC18RC / DC18RA
Charging time
22minutes

Fast
Charging
22
min



****DTM50Z
Excludes Battery,
Charger
and Multi Tool
Accessories**
Purchased separately**

Cordless Multi Tool DTM50Z



Oscillations per minute	6,000-20,000
Dimensions (L x W x H)	324x80x122mm with BL1830 307x80x122mm with BL1815
Net Weight*	2.0kg with BL1830 1.8kg with BL1815

Variable Speed Soft Start Built-in Job Light

Standard Equipment: Hex Wrench, Outer Flange including Socket, Inner Flange

*weight according to EPTA-Procedure 01/2003
Items of standard equipment and specifications may vary by country or area.



Cordless Multi Tool DTM50Z



Satisfy Professional's Needs



EXTRA VERSATILE

Wide selection of accessories available
for various applications

Oscillating Multi Tool

****DTM50Z
Excludes Battery,
Charger
and Multi Tool
Accessories**
Purchased separately**



Compatible with all OIS
(Oscillating Interface System)
accessories



The standard equipment may vary by country.



Cutting PVC, FRP pipes



Cutting metals



Wood flush cutting



Wood plunge cutting



Deep plunge cutting



Sanding and polishing various materials



Cutting tiles



Removing mortar, tile adhesive

High operation efficiency

Oscillations per minute: up to 20,000 min⁻¹

Oscillating angle: 3.2°



Multi angle setting



Fully 360° multi angle setting enables users to position accessories in 12 different angles (each 30°) to allow access to tight spaces for optimum maneuverability.



Dust extraction system (Option)



Dust extraction system is available as an option for aggressive dust removal in applications with sanding pad.



Battery capacity warning lamp



Blinking red:
Battery power is nearly used up.
Solid red:
Battery power is used up; battery protection circuit will shut off the power.



Cutting plasterboards



Metal flush cutting



Flush cutting of nails



Routing joints on wall tiles



Corner cutting



Cutting window putty, silicone



Cutting polystyrene, rubber



Scraping floor tiles