



LED Flashlight DML802

Satisfy Professional's Needs

LXT
LITHIUM-ION

18V
LITHIUM-ION

14.4V
LITHIUM-ION



Battery is option.

HIGH LUMINANCE 3.2W LED

Long continuous illumination of 13 hours

with a fully charged 18V-3.0Ah battery BL1830

12 Position pivoting flashlight head

Positive stops at 110°, 90°, 75°, 60°, 45°, 30°, 15°, 0°, -15°, -30°, -45°, -60°



Light source

Type : 3.2W single LED
Illuminance : 4,000lx
Luminous flux : 160lm
Service life : 50,000hours or more



Illuminance: measured in ø20mm circle at the center of an illuminated field 1m in front of the light source.

Multi-faceted reflector

controls the direction and spread of light cast from LED to provide a sharp round spot light with uniform high brightness.



Strap hook

can be installed on the upper or lower position in accordance with usage.



Compact size aluminum flashlight head

gives an impression of heavy-duty product.

Ergonomically designed handle with rubberized soft grip

On/Off switch



Battery is option.

Battery



BL1830: 18V 3.0Ah
BL1815: 18V 1.3Ah
BL1430: 14.4V 3.0Ah
BL1415: 14.4V 1.3Ah

Charger

DC18RC / DC18RA
Charging time
22minutes



DC18SD
Charging time
60minutes



LED Flashlight

DML802 18V, 14.4V

	18V LITHIUM-ION	14.4V LITHIUM-ION
Continuous use (hours)	13-3.0Ah	9-3.0Ah
Dimensions (L x W x H)	272x79x116mm (10-3/4"x3-1/8"x4-9/16") with BL1830 256x79x116mm (10-1/8"x3-1/8"x4-9/16") with BL1815	272x79x99mm (10-3/4"x3-1/8"x3-7/8") with BL1430 256x79x99mm (10-1/8"x3-1/8"x3-7/8") with BL1415
Net Weight*	0.93kg (2.1lbs) with BL1830 0.71kg (1.6lbs) with BL1815	0.84kg (1.9lbs) with BL1430 0.65kg (1.5lbs) with BL1415

*weight according to EPTA-Procedure 01/2003

Items of standard equipment and specifications may vary by country or area.



Makita New Zealand Ltd.
15 Orbit Drive, Mairangi Bay
PO Box 100 914, North Shore, Auckland 0745
Fax 0800 600 601 Sales 09 479825

Visit our website for information and tool features :
www.makita.co.nz