

GA5010

125mm Angle Grinder

1 050W



Large shaft lock button

Small gear housing for increased maneuverability

Thakita O

Trigger switch with easy to operate single finger trigger



High Dust-Proof Construction

- Protective zigzag varnish on armature.
- Protective powder varnish-coating on field
- Bearing-protective labyrinth structure
- Three dust-proof ball bearings seal out dust
- Dust proof vent design.



Zigzag varnishing



Protective Powder Varnish



A. Labyrinth structure B. Dust-proof ball bearing

MAKITA ADVANTAGE

- ! Lightweight, slim body with high durability.
- ! Ergonomically designed handle with rubberized grip provides more comfort and control.



SPECIFICATIONS:

Maximum Capacities:

Depressed centre wheel 125mm
Abrasive disc 125mm
Diamond wheel 125mm
Continuous rating input 1 050W
No load speed 11 000 r/min
Overall dimensions (L x W x H) 356 x 139 x 112mm

Net weight 2.6kg
Power supply cord 2.5m
Carbon brush CB303

FEATURES:

Double insulation

STANDARD EQUIPMENT:

Depressed centre wheel, lock nut wrench & side grip

OPTIONAL ACCESSORIES

Description Part No.

Diamond blade, segmented
Diamond blade, waffle
Sanding lock nut 14 -48
Side grip
125mm wheel cover
125mm toolless wheel cover
135108-2
A-84115 or A-80438
B-02054
224515-5
153504-2
125419-3
135108-2

Ref: GA5010