

TECHNICAL DATA SHEET

P.DS.061 (BW SERIES) REV05/13/2019

WATER BASED NANOTECH

PLASTER PRIMER



YEAR QUALITY
GUARANTEE



Promac Easycoat Plaster Primer is a water based plaster primer which penetrates the surface and ensures optimum adhesion of top coats to the surface.

FEATURES & BENEFITS

- Lead less than 90 ppm
- Alkali and water resistant
- Excellent adhesion properties
- Suitable for a variety of substrates
- Breathable - allows moisture to escape
- Rapid drying
- Environmentally friendly
- Water clean-up

USES

Interior / Exterior

New or previously painted concrete, cement plaster, fibre cement, gypsum plaster, building boards and brick surfaces after suitable preparation. Interior and exterior use.

COLOUR

White

FINISH

Matt

SPREADING RATE

This product will cover approximately 4 - 8 m² per litre per coat depending on the type of substrate and the surface porosity.

CLEANING

Do not allow the product to dry on equipment. Equipment is readily cleaned using water. (Some detergent may be added to water to facilitate clean up)

APPLICATION

Stir the contents thoroughly with a flat paddle before use. Apply this product with a paint-brush or Synthetic PVA roller, and allow 2 to 4 hours drying time between coats

PREVIOUSLY PAINTED SURFACES

Thoroughly clean and prepare surfaces by removing all dust, dirt, grease, mould, grime and flaking paint before starting to paint.

Toll Free: 080 111 1019 | Head Office: 012 804 7305 | www.promacpaints.co.za



TECHNICAL DATA SHEET

P.DS.061 (BW SERIES) REV05/13/2019

DO NOT PAINT

1. If the temperature is below 10°C or above 35°C
2. If the surface is damp (Moisture reading above 15%)
3. If it is raining or rain is forecast
4. Before 9:00 and after 16:00 in the winter

HEALTH & SAFETY

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust / fume / gas / mist / vapours / spray. Wash hands thoroughly after handling. Wear protective gloves / protective clothing / eye protection / face protection. Use personal protective equipment as required. Keep paint away from children and animals. Never smoke, drink or eat while painting. Causes mild skin irritation. Toxic to aquatic life. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun. Dispose of contents / container in accordance with local / regional / national / international regulations.

DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.

TECHNICAL DATA

PHYSICAL FORM	Non-flammable viscous liquid containing pigments and extenders
COLOUR	White. Can be tinted to pastel/deep colours if required
FINISH	Smooth, Matt
SPREADING RATE	Approximately 4 – 8 m ² /ℓ per application
POLYMER TYPE	Alkali- and water-resistant acrylic copolymer latex
FILLERS	Non-toxic extenders
PIGMENTS	Weather and light resistant types only
DRYING PROPERTIES	Surface or touch-dry: within 1 hour
RECOATING TIME	4 hours depending on conditions and film build
FLASH POINT	Not flammable in liquid form
PACKAGING	5 L & 20 L
THINNING	Not recommended, but if required to reduce viscosity add a minimum quantity of WATER. Excessive dilution degrades the quality of the product. (NB: DO NOT add solvent-based thinners such as mineral turpentine or lacquer thinners)
CLEANING	Do not allow the product to dry on equipment. Equipment is readily cleaned using water. (Some detergent may be added to water to facilitate clean up)
APPLICATION METHOD	Supplied ready-for-use. Apply using Fine foam roller or brush

Toll Free: 080 111 1019 | Head Office: 012 804 7305 | www.promacpaints.co.za

