

## TECHNICAL DATA SHEET

P.DS.036 (FB SERIES) REV01/11/2018

### WATER BASED

# BATHROOMS & KITCHENS

**10**

YEAR QUALITY  
GUARANTEE



Promac Bathrooms & Kitchens is a high quality pigmented hygienic water based paint. It has a subtle sheen finish with excellent adhesion, stain resistance and washability. The product is formulated with silver biocides that protects the paint film surface and inhibits the growth of microorganisms. It is also mould, water and steam resistant in high humidity areas. Application can be for either primed new work, or previously sound painted areas.

### FEATURES & BENEFITS

- Lead less than 90ppm
  - Excellent wet and dry adhesion properties
  - Rapid drying - 2 Coats can be applied in one day
  - Water based
  - Alkali, steam, water & mould resistant
  - Easily cleanable or washable
  - Environmentally friendly
- Specially formulated to resist mildew growth on the paint film

### USES

#### Interior / Exterior

New or previously painted, masonry plaster, gypsum, concrete, fibre cement and brick surfaces after suitable preparation. Ideal for kitchen & Bathrooms where a hard-wearing finish is required.

### COLOUR

White only

### FINISH

Smooth subtle sheen finish

### SPREADING RATE

This product will cover approximately 8 - 10 m<sup>2</sup> per litre per coat depending on the type of substrate and the surface porosity.

### CLEANING

Do not allow the product to dry on equipment. Equipment is readily cleaned using water. (Some detergent may be added to water to facilitate clean up)

### APPLICATION

Apply this product with a paint brush or mohair roller to smooth surfaces and use a quality synthetic long pile paint roller on rough/coarse surfaces. Always allow at least 4 hours drying time between coats.

## TECHNICAL DATA SHEET

P.DS.036 (FB SERIES) REV01/11/2018

### SURFACE PREPARATION

All surfaces to be painted must be clean, dry (15% moisture max) in sound condition before painting. New plaster, concrete, fibre cement & gypsum surfaces: apply one coat of Promac Plaster Primer followed by two coats Promac Bathrooms & Kitchens. Previously painted plaster surfaces must be clean and free of all dirt, grease, grime and flaking paint before painting. Apply two coats of Promac Bathrooms & Kitchens leaving at least 4 hours between coats.

### DO NOT PAINT

1. If the temperature is below 10°C or above 35°C
2. If the surface is damp (Moisture reading above 15%)
3. If it is raining or rain is forecast
4. Before 9:00 and after 16:00 in the winter

### HEALTH & SAFETY

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust / fume / gas / mist / vapours / spray. Wash hands thoroughly after handling. Wear protective gloves / protective clothing / eye protection / face protection. Use personal protective equipment as required. Keep paint away from children and animals. Never smoke, drink or eat while painting. Causes mild skin irritation. Toxic to aquatic life. If accidental contact with skin should occur, wash immediately with clean water. Harmful if swallowed. Do not induce vomiting. Consult your doctor. Ensure good ventilation during application and drying. Store in a cool, dry place out of the sun. Dispose of contents / container in accordance with local / regional / national / international regulations.

### DISCLAIMER ADVICE

The information given in this Product Information Sheet is based on controlled laboratory tests and many years of experience. It is given in good faith but no guarantee of any performance characteristic is given or implied. Promac Paints cannot be held liable for consequential damage of whatsoever nature that may arise from the use of Promac products. Paint technology is continuously being developed and Promac Paints reserves the right to update product specifications without prior notice. Contact Promac Paints for further details.

### TECHNICAL DATA

<b>POLYMER TYPE</b>	Acrylic co-polymer
<b>FILLERS</b>	Non-toxic fine particle sized extenders
<b>PIGMENTS</b>	Non-toxic weather and light resistant types only
<b>DRYING PROPERTIES</b>	Surface or touch-dry: within 30 mins
<b>RECOATING TIME</b>	4 - 6 hours depending on conditions during drying
<b>FLASH POINT</b>	Non-flammable (waterbased product)
<b>PACKAGING</b>	2.5ℓ
<b>PHYSICAL FORM</b>	A low odour medium viscosity liquid paint

Toll Free: 080 111 1019 | Head Office: 012 804 7305 | [www.promacpaints.co.za](http://www.promacpaints.co.za)